

## Conexões Alta Pressão com encaixe para solda ASME B16.11

BIT.	B		D			C						G			J	A						E	F
	MAX.	MIN.	3000	6000	9000	3000		6000		9000		3000	6000	9000		90°			45°				
						MAX.	MIN.	MAX.	MIN.	MAX.	MIN.					MIN.	MIN.	3000	6000	9000	3000		
1/8"	10.9	10.7	7.6	4.8		3.2	3.2	4.0	3.4			2.4	3.1		9.7	11.2	11.2		7.9	7.9		6.4	15.7
1/4"	14.4	14.0	10.0	7.1		3.8	3.3	4.6	4.0			3.0	3.7		9.7	11.2	13.5		7.9	7.9		6.4	15.7
3/8"	17.7	17.5	13.3	9.9		4.0	3.5	5.0	4.4			3.2	4.0		9.7	13.5	15.7		7.9	11.2		6.4	17.5
1/2"	22.0	21.7	16.5	12.5	7.2	4.7	4.0	6.0	5.2	9.3	8.2	3.7	5.5	7.5	9.7	15.7	19.0	25.4	11.2	12.7	15.7	9.7	22.4
3/4"	27.3	27.0	21.7	16.3	11.8	4.9	4.3	7.0	6.0	9.8	8.5	3.9	5.5	7.8	12.7	19.0	22.4	28.4	12.7	14.2	19.0	9.7	23.9
1"	34.0	33.8	27.4	21.5	18.0	5.7	5.0	7.9	6.9	11.4	10.0	4.5	6.4	9.1	12.7	22.4	26.9	31.8	14.2	17.5	20.6	12.7	28.5
1 1/4"	42.8	42.5	35.8	30.2	23.5	6.1	5.3	7.9	6.9	12.1	10.6	4.9	6.4	9.7	12.7	26.9	31.8	35.0	17.5	20.6	22.4	12.7	30.2
1 1/2"	48.9	48.6	41.7	34.7	28.7	6.4	5.5	8.9	7.8	12.7	11.1	5.1	7.1	10.2	12.7	31.8	38.1	38.1	20.6	25.4	28.5	12.7	31.8
2"	61.4	61.1	53.3	43.6	38.9	6.9	6.0	10.9	9.5	13.8	12.1	5.5	8.7	11.1	15.7	38.1	41.1	53.8	25.4	28.5		19.0	41.1
2 1/2"	74.2	73.8	64.2	61.2		8.8	7.7					7.0			15.7	41.1			28.5			19.0	42.9
3"	90.2	89.9	79.5	78.4		9.5	8.3					7.6			15.7	57.2			31.8			19.0	44.5
4"	115.8	115.4	103.8	100.7		10.7	9.3					8.5			19.0	66.5			41.1			19.0	47.8

Dimensões		
Ø nominal (pol.)	Niple Sextavado	
	A (mm)	B (mm)
1/8	28,6	11,1
1/4	34,1	15,9
3/8	38,1	17,5
1/2	42,1	22,2
3/4	48,0	27,0
1	50,0	34,9
1.1/4	55,6	44,5
1.1/2	61,1	50,8
2	64,3	63,5
2.1/2	74,6	76,2
3	92,5	90,5
4	109,9	117,5




Figura 2931 - Niple para alta pressão - 3000 IBS - Neg 1 corpo  
 Figura 2810 - Niple Sextavado em Aço Rosca BSP  
 Figura 2820 - Niple Sextavado em Aço Rosca NPT  
 Figura 2830 - Niple Sextavado em Aço Carbono BSP  
 Figura 2840 - Niple Sextavado em Aço Carbono NPT

