

Conexões Alta Pressão com Roscas ASME B16.11

	A			C			H			G			MIN	
	2000	3000	6000	2000	3000	6000	2000	3000	6000	2000	3000	6000	B	L ₂
1/8"	20.6	20.6	24.6	17.3	17.5	19.0	22.4	22.4	25.4	3.2	3.2	6.4	6.4	6.7
1/4"	20.6	24.6	28.5	17.5	19.0	22.4	22.4	25.4	33.3	3.2	3.3	6.6	8.1	10.2
3/8"	2406	28.5	33.3	19.0	22.4	25.4	25.4	33.3	38.1	3.2	3.5	7.0	9.1	10.4
1/2"	28.5	33.3	38.1	22.4	25.4	28.5	33.3	38.1	46.0	3.2	4.0	8.2	10.9	13.5
3/4"	33.3	38.1	44.5	25.4	28.5	33.3	38.1	46.0	55.6	3.2	4.3	8.5	12.7	13.9
1"	38.1	44.5	50.8	28.5	33.3	35.0	46.0	55.6	62.0	3.7	5.0	9.9	14.7	17.3
1 1/4"	44.5	50.8	60.5	33.3	35.0	42.9	55.6	62.0	75.4	3.9	5.3	10.6	17.0	18.0
1 1/2"	50.8	60.5	63.5	35.0	42.9	43.7	62.0	75.4	84.0	4.0	5.6	11.1	17.8	18.4
2"	60.5	63.5	82.5	42.9	43.7	52.3	75.4	84.0	101.6	4.3	7.1	12.0	19.0	19.2
2 1/2"	76.2	82.5	95.3	52.3	52.3	63.5	92.0	101.6	120.7	5.6	7.6	15.3	23.6	28.9
3"	85.9	95.3	106.4	63.5	63.5	79.2	109.5	120.7	146.0	6.0	8.8	16.6	25.9	30.5
4"	106.4	114.3	114.3	79.2	79.5	79.2	146.0	152.4	152.4	6.5	11.2	18.7	27.7	33.0

BITOLA	W		P		D		G MIN.		H	
	3000 e 6000	3000	6000	3000	6000	3000	6000	3000	6000	
1/8"	31.8	19.0		15.7	22.4	4.8		44.5		
1/4"	35.0	25.4	26.9	19.0	25.4	4.8	6.4	44.5	52.5	
3/8"	38.1	25.4	26.9	22.4	31.8	4.8	6.4	51.0	54.0	
1/2"	47.8	31.8	33.3	28.5	38.1	6.4	7.9	54.0	73.0	
3/4"	50.8	36.5	38.1	35.0	44.5	6.4	7.9	59.0	86.0	
1"	60.5	41.2	43.0	44.5	57.2	9.7	11.2	63.5	92.0	
1 1/4"	66.5	44.5	46.0	57.2	63.5	9.7	11.2	71.5	98.5	
1 1/2"	79.2	44.5	47.8	63.5	76.2	11.2	12.7	79.5	106.5	
2"	86.0	47.8	50.8	76.2	92.0	12.7	15.7	89.0	117.5	
2 1/2"	92.0	60.5	63.5	92.0	108.0	15.7	19.0			
3"	108.0	65.0	68.3	108.0	127.0	19.0	22.4			
4"	120.7	68.3	74.7	139.7	158.8	22.4	28.5			

